



with domestic and global components.

Model No. **810-T72**

8" Dual Cone Driver & Dual-Voltage Transformer

Dual cone driver with mounted dual voltage 70/25V transformer provides solid performance for basic paging and background music.

Features

- 8" dual cone driver with 10 oz. ceramic magnet , 3/4" hard fiber whizzer cone, 1" voice coil, and 20-ga. steel frame with zinc-plated finish
- Power rating 15W
- Mounted and wired 70/25V dual voltage transformer (No. TLM-572) has primary taps at 0.25, 0.5, 1, 2, 5W.
- Meets or exceeds all applicable EIA standards



A&E Specifications

The dual cone 8-inch speaker shall be Lowell Model No. 810-T72 which shall be of the permanent magnet type having a seamless molded fiber cone with a hard fiber whizzer cone mechanically coupled to a voice coil for extended high frequency response. Power rating shall be 15 watts RMS. The voice coil shall have a 1-in. dia. and shall operate in a magnetic field derived from a strontium ferrite (ceramic) magnet having a nominal weight of 10 oz. Voice coil impedance shall be 8ohms. The driver shall have a round, structurally reinforced stamped 20-ga. steel frame with 8.062" overall diameter and eight obround holes equally spaced at 45 degrees on a 7.625" dia. mounting bolt circle. Overall depth shall not exceed 2.84". External metal parts shall be zinc-plated to resist rust and corrosion. The mounted transformer shall be 70/25V dual voltage with selectable taps at .25, .5, 1, 2, and 5W. The assembly shall be capable of producing a uniform audible frequency response over the range of 51Hz-11.6kHz (± 6 dB), 50Hz-20kHz (± 6.4 dB) with dispersion angle of 95 degrees conical @2000Hz (-6dB). Average sensitivity shall measure 97.9dB (SPL at 1W/1M).

Driver + Transformer Specifications

Driver + Xfmr. No's.	Driver Type	Driver Power Rating	Driver Magnet Wt.	Transformer Taps	Assembly Frequency Response	Assembly Dispersion @2000Hz Octave (-6dB)	Assembly Sensitivity	Assembly Mtg. Depth	Max SPL
810 + TLM-572	Dual cone 8ohm	15W	10 oz.	.25, .5, 1, 2, 5W @70/25V	51Hz-11.6kHz (± 6 dB) 50Hz-20kHz (± 6.4 dB)	95 degrees conical	97.9dB Avg SPL	2.84"	104.9 **

* Minimum depth required for assembly to be rear-mounted to grille in an enclosure.
 ** Calculated based on 5W maximum transformer power tap and measured sensitivity.
 Additional information available on specification sheet for Driver No. 810.